


# Global-Flex Mfg.

1580 Charles Drive Redding, CA 96003

## Style REJ-TN Rubber Teflon Expansion Joint “Made In USA All Domestic”



**Global-Flex Mfg. Style REJ-TN** expansion joints combined the best features of Teflon with the best features of elastomeric expansion joints. Joints are available in 1” up to 24” I.D. in standard face-to-face dimensions, or special lengths. Also available in multiple arch configurations or as straight pipe.

*Style REJ-TN* joints are recommended for use in the chemical and pulp paper industries because of their capabilities to resist corrosive attack along with high temperatures and pressures.

### Features:

- Chlorine Resistance
- Anti-stick properties
- Noise and Vibration dampening
- High Flexibility
- Thermal Stability
- Resistance to age cracking
- High pressure ratings
- Temperature rating up to 400 F

I.D.	Face/Face Inch	Flange O.D.	Bolt Cir Dia.	No of Bolt Holes	Bolt Hole Dia.	Arch Height/Width		Working Pressure	Axial Comp	Axial Ext	Trav Defl	Weight
						D	D					
2	6	6	4.75	4	.75	1.25	1.75	225	1.75	.75	.75	4
2-1/2	6	7	5.5	4	.75	1.25	1.75	225	1.75	.75	.75	4.5
3	6	7.5	6.0	4	.75	1.25	1.75	225	1.75	.75	.75	5.5
4	6	9	7.5	8	.75	1.25	1.75	225	1.75	.75	.75	8
5	6	10	8.5	8	.875	1.25	1.75	225	1.75	.75	.75	9
6	6	11	9.5	8	.875	1.25	1.75	225	1.75	.75	1	11
8	6	13.5	11.75	8	.875	1.5	1.75	225	1.75	.75	1	15
10	8	16	14.25	12	1	1.5	1.75	225	1.75	.75	1	23
12	8	19	17	12	1	1.5	1.75	225	1.75	.75	1	34